

FILTER DATA & SPECIFICATIONS

	Hi-Grade Filter	Regular Filter	KDF Filter
Applicable Against	Dissolvable lead, residual chlorine, removes up to 5 micron particles (dust and corrosion residue), odors	Residual chlorine, removes up to 5 micron particles (dust and corrosion residue), odors	Removes up to 5 micron particles when included in the 2-Stage KDF Pre-Filter Contaminants Removed (see Below)
Not Applicable Against	Metal ions, Sodium chloride solutions	Metal ions, Sodium chloride solutions	Calcium, magnesium, potassium, cysts, bacteria
Service Life	3,158 gallons (About 12,000L), * 0.4 ppm against 2ppm tap water	3,158 gallons (About 12,000L), * 0.4 ppm against 2ppm tap water	KDF - KDF Filter (About 8-12 months) KDF - Pre Filter (when it is dirty)
High Performance Filter Life	1,579 gallons (About 6,000L), * Life of water filter varies on supplied water quality and quantity	N/A	N/A
Materials	Granulated antibacterial activated charcoal, Lead removing activated charcoal, Calcium sulfite, Mechanical filter, Case: ABS resin, O-ring: NBR	Granulated antibacterial activated charcoal, Calcium sulfite, Mechanical filter, Case: ABS resin, O-ring: NBR	Kinetic Degradation Fluxion
Diameter	3.46x5.91 inch (ø88x150mm)	3.46x5.91 inch (ø88x150mm)	
Weight	0.81lbs (370g)	0.81lbs (370g)	

Contaminants Removed
Lead - Particulate
Lead - Dissolved
Copper
Barium
Arsenic (inorganic)
Cadmium
Chromium
Hydrogen Sulfide
Mercury
Iron
Trihalomethanes (THM)
Chlorine
Rust/Sediment
Taste/Odor
Has Shown Reduction, But Inconsistent
Nitrate
Flouride